

PUBLIC WORKS LABORATORIES TEST DIRECTORY

LABORATORIES

| | |
|----|---|
| CL | Central Laboratory (Tel: 2305 1290) |
| NL | North Lantau Regional Laboratory (Tel: 2109 0657) |
| KL | Kowloon Regional Laboratory (Tel: 2703 7332) |
| TP | Tai Po Regional Laboratory (Tel: 2144 1777) |
| TS | Tin Shui Wai Regional Laboratory (Tel: 2447 1677) |
| SS | Sham Shui Kok Regional Laboratory (Former Tsuen Wan Regional Laboratory) (Tel: 2439 9282) |

KEY TO AVAILABILITY OF TEST

| | |
|----|--|
| A | Laboratory accredited by HOKLAS for the test |
| A* | Equipment for the test are classified as "out of service", and shall be calibrated before use. HOKLAS certificates are issued only if the relevant calibration requirements are met. |
| √ | Laboratory not accredited for the test |
| √* | Laboratory not accredited for the test. Equipment for the test are classified as "out of service", and shall be repaired and calibrated before use. |
| ∇ | Laboratory not set up to perform the test but has equipment |
| # | Test not performed in the laboratory Test programme shall be agreed with the laboratory in advance. |

- Notes:
1. Test/Calibration reports/certificates will normally be posted but, by arrangement, may be collected from the laboratory to which the samples were delivered.
 2. *Italic font* indicates a test not frequently performed, i.e. infrequent test (performed less than once per year). The test may require longer time to perform if equipment needs to be calibrated prior to performing the test and/or staff need to be re-trained and audited before performing the test. Additional samples may be required for re-training/auditing

Aggregates

| PW/LTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | | |
|-------------|---|--------------------------------|-----------|--------------------------|-------------------------|----|----|----|----|----|---|
| | | | | | CL | NL | KL | TP | TS | SS | |
| AGG 1.8 | Sieve analysis of mineral filler for bituminous paving mixtures | ASTM D546-05 with Modification | | 2113 | | | | | | √* | A |
| AGG 1.8(a) | Sieve analysis of mineral filler for asphalt paving mixtures | ASTM D546-17 with modification | | 2113 | | A | A | A | A | A | A |
| AGG 1.9 | Determination of particle size distribution of aggregate by sieving (washing and sieving method/ dry sieving method) | Section 10 of CS3:2013 | | 2117 | | A | A | A | A | A | A |
| AGG 1.10 | Determination of aggregate flakiness index | Section 11 of CS3:2013 | | 2117 | | A | A | A | A | A | A |
| AGG 1.11 | Determination of aggregate elongation index | Section 12 of CS3:2013 | | 2117 | | A | A | A | A | A | A |
| AGG 1.12 | Determination of density of mineral filler for bituminous paving mixtures | BS EN 196-6:2010 Annex NC | | 2113 | | | | | | | |
| AGG 2.3 | Determination of the compaction fraction value of aggregates for granular bed | GS(2006) App. 5.2 | 5.86 | 2113 | | A | A | A | A | A | A |
| AGG 2.3(a) | Determination of the compaction fraction value of aggregates for granular bed | GS(2020) App. 5.2 | | 2113 | | A | A | A | A | A | A |
| AGG 2.4(a) | Determination of particle densities and water absorption of aggregate with nominal size larger than 10 mm (wire basket method) | BS 812:Part 2:1995 Section 5.3 | | 2113 | | √ | | √ | √ | √ | √ |
| AGG 2.4(b) | Determination of particle densities and water absorption of aggregate with nominal size not larger than 10 mm (pycnometer method) | BS 812:Part 2:1995 Section 5.5 | | 2113 | | √ | | √ | √ | √ | √ |
| AGG 2.5 | Determination of bulk density of aggregate | BS 812:Part 2:1995 | | 2113 | | √ | | | | | |
| AGG 2.6 (a) | Determination of particle densities & water absorption of aggregate all larger than 10 mm (wire basket method) | Section 17 of CS3:2013 | | 2117 | | A | | A | A | A | A |
| AGG 2.6 (b) | Determination of particle densities & water absorption of aggregate 10 mm nominal size and smaller (pycnometer method) | Section 17 of CS3:2013 | | 2117 | | A | | A | A | A | A |
| AGG 2.7 | Determination of aggregate moisture content | Section 18 of CS3:2013 | | 2117 | | A | A | A | A | A | A |
| AGG 3.9 | Determination of Los Angeles value | Section 14 of CS3:2013 | | 2117 | | ∇ | | | | | A |
| AGG 3.10 | Determination of aggregate impact value | Section 15 of CS3:2013 | | 2117 | | | | | | A | √ |
| AGG 3.11 | Determination of aggregate ten per cent fines value | Section 16 of CS3:2013 | | 2117 | | A | A | A | A | A | A |
| AGG 3.12 | Determination of aggregate soundness value | Section 19 of CS3:2013 | | 2117 | | A | | | | A | |
| AGG 5.1 | Determination of maximum metals and foreign material content for the recycled sub-base materials | GS 2006, Clause 9.47 (9) | | 2113 | | √* | | √* | ∇ | ∇* | |
| AGG 6.1 | Determination of alkali silica reaction potential by ultra-accelerated mortar bar test | CSI:2010, Vol. 2:Section 22 | | 2113 | | A | | | | | |
| AGG 6.2 | Determination of drying shrinkage | Section 20 of CS3:2013 | | 2117 | | A | | | | | |
| AGG 6.3 | Determination of effect of organic substances by mortar method | Section 22 of CS3:2013 | | 2117 | | A | | | | | |
| AGG 6.4 | Determination of methylene blue value | Section 13 of CS3:2013 | | 2117 | | A | | | | | |

Bituminous materials

| PW/LTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | |
|--------------|---|---|-----------|--------------------------|-------------------------|----|----|----|----|----|
| | | | | | CL | NL | KL | TP | TS | SS |
| BIT 1.2 | Determination of solubility of bituminous binders | BS2000: Part 47:1985 | 9.49 | 2119 | | | | | | √ |
| BIT 1.3(a) | Determination of softening point of bitumen having softening point 80°C or below by ring and ball method | BS2000:Part 58:1993 | 9.49 | 2119 | | | | | | √ |
| BIT 1.4 | Determination of loss on heating of bitumen and flux oil | BS2000:Part 45:1993 | 9.49 | 2119 | | | | | | √ |
| BIT 1.7 | Determination of viscosity of asphalt by vacuum capillary viscometer | ASTM D2171-88, 94 and 01 | 9.49 | 2119 | | | | | | √ |
| BIT 1.11 | Determination of viscosity of asphalt binder using rotational viscometer | AASHTO T316-06/T316-13(2017) | | 2112 / 2123 | | | √ | √ | | A |
| BIT 1.11(a) | Determination of viscosity of asphalt binder using rotational viscometer | AASHTO T316-06/T316-13(2017) with modifications | | 2112 | | A | A | A | | A |
| BIT 1.12 | Determining the rheological properties of asphalt binder using a dynamic shear rheometer (DSR) | AASHTO T315-09 | | 2123 | | | | | | A |
| BIT 1.12(a) | Determination of the rheological properties of asphalt binder using a dynamic shear rheometer (DSR) | AASHTO T315-12 (2016) | | 2123 | | | | | | √ |
| BIT 1.13 | Effect of heat and air on a moving film of asphalt (rolling thin-film oven test) | AASHTO T240-09 | | 2123 | | | | | | A |
| BIT 1.13(a) | Effect of heat and air on a moving film of asphalt (rolling thin-film oven test) | AASHTO T240-13 | | 2123 | | | | | | √ |
| BIT 1.15 | Determination of flash point by using Cleveland open cup tester | AASHTO Designation T48-06 | | 2123 | | | | | | A |
| BIT 1.15(a) | Determination of flash point by Cleveland open cup | AASHTO T48-06 (2015) | | 2123 | | | | | | √ |
| BIT 1.16 | Determination of penetration of semi-solid and solid bituminous materials | ASTM D5-86 | | 2119 | | | | | | √ |
| BIT 1.17 | Determination of the specific gravity or density of semi-solid and solid bituminous materials by nickel crucible method | ASTM D3289-85 | | 2119 | | | | | | √ |
| BIT 1.18 | Determination of the ductility of bituminous materials | ASTM D113-86 | | 2119 | | | | | | √ |
| BIT 1.19 | Determination of penetration of asphaltic materials | ASTM D1754-87 and D5-86 | | 2119 | | | | | | √ |
| BIT 1.20 | Determination of solubility of asphalt materials in trichloroethylene | ASTM D 2042-81/85 | | 2119 | | | | | | √ |
| BIT 1.21 | Determination of penetration of semi-solid and solid bituminous materials | ASTM D5-13 | | 2119 | | | | | | √ |
| BIT 1.22 | Determination of softening point by ring and ball method | BS EN 1427:2015/BS 2000-58:2015 | | 2119 | | | | | | √ |
| BIT 1.23 | Determination of ductility of bituminous materials | ASTM D113-07 | | 2119 | | | | | | √ |
| BIT 1.24 | Determination of solubility of asphalt materials in trichloroethylene | ASTM D2042-15 | | 2119 | | | | | | √ |
| BIT 1.25 | Determination of retained penetration of asphaltic materials (thin-film oven test and penetration test) | ASTM D1754-09 (2014) and D5-13 | | 2119 | | | | | | √ |
| BIT 1.26 | Determination of viscosity of asphalt by vacuum capillary viscometer | ASTM D2171-10 | | 2119 | | | | | | √ |
| BIT 1.27 | Determination of loss in mass after heating of industrial bitumen | BS EN 13303:2009/BS 2000-509:2009 | | 2119 | | | | | | √ |
| BIT 1.28 | Determination of density of semi-solid and solid asphalt materials by nickel crucible method | ASTM D3289-17 with modification | | 2119 | | | | | | √ |
| BIT 1.29 | Determination of dynamic viscosity of highly modified bitumen by vacuum capillary viscometer with modification | T0620-2000 & ASTM D2171-10 with modification | | 2123 | | | | | | √ |
| BIT 3.9(a) | Determination of bitumen content of bituminous paving materials (with aggregate size smaller than 28mm) by centrifuge extractor | ASTM D2172-95 Method A | | 2112 | | A | A | A | | A |
| BIT 3.9(b) | Determination of bitumen content of bituminous paving materials (with aggregate size greater than or equal to 28mm) by centrifuge extractor | ASTM D2172-95 Method A | | 2112 | | A | A | A | | A |
| BIT 3.9(c) | Determination of asphalt binder content of asphalt mixtures by centrifuge extractor | ASTM D2172/D2172M-17 Method A | | 2112 | | A | A | A | | A |
| BIT 3.10 | Determination of aggregate grading of bituminous paving materials | ASTM C117-95 Procedure B & ASTM C136-96a with modifications | | 2112 | | A | A | A | | A |
| BIT 3.10(a) | Sieve analysis of fine and coarse aggregates | ASTM C117-13 Procedure B & C136/C136M-14 with modifications | | 2112 | | A | A | A | | A |
| BIT 3.11 | Determination of bulk specific gravity and density of non-absorptive compacted dense bituminous paving materials | ASTM D2726-96a | | 2122 | | A | A | A | | A |
| BIT 3.11(a) | Determination of bulk specific gravity, density and percent air voids of non-absorptive compacted dense bituminous/asphalt mixtures | ASTM D2726/2726M-14 and D3203/D3203M-17 with modifications | | 2122 | | A | A | A | | A |
| BIT 3.12(a) | Determination of theoretical maximum S.G. (Rice's S.G.) of bituminous paving materials (with aggregate size smaller than 28mm) using Type A container, weighing in water method with modification | ASTM D2041-95 | | 2112 | | A | A | A | | A |
| BIT 3.12(b) | Determination of theoretical maximum S.G. (Rice's S.G.) of bituminous paving materials (with aggregate size greater than or equal to 28mm) using Type A container, weighing in water method with modification | ASTM D2041-95 | | 2112 | | A | A | A | | A |
| BIT 3.12(c) | Determination of theoretical maximum S.G. (Rice's S.G.) of bituminous paving mixtures (vacuum bowl, weighing in water method) | ASTM D2041/D2041M-11 | | 2112 | | A | A | A | | A |
| BIT 3.13 | Determination of air void content of compacted bituminous paving materials | ASTM D3203-94 | | 2122 | | A | A | A | | A |
| BIT 3.14 | Determination of bitumen content of bituminous paving materials by ignition method | ASTM D6307-98 | | 2112 | | A | A | A | | A |
| BIT 3.14(a) | Determination of bitumen content of bituminous paving materials by ignition method | ASTM D6307-05 | | 2112 | | A | A | A | | A |
| BIT 3.14(b) | Determination of asphalt binder content of asphalt mixtures by ignition method | ASTM D6307-16 | | 2112 | | A | A | A | | A |
| BIT 3.15 | Determination of polymer modified binder content of bituminous paving materials by the combination of both centrifuge and ignition method | ASTM D2172-95 Method A, ASTM D6307-98 & Appendix 9.2 of Contract Particular Specification issued by Highways Department | | 2112 | | A | A | A | | A |
| BIT 3.15 (a) | Determination of polymer modified asphalt binder content of asphalt mixtures by the combination of both centrifuge and ignition method | ASTM D2172-95 Method A, ASTM D6307-05 & Appendix 9.2 of Contract Particular Specification issued by Highways Department | | 2112 | | A | A | A | | A |
| BIT 3.15(b) | Determination of polymer modified asphalt binder content of asphalt mixtures by the combination of both centrifuge and ignition method | ASTM D2172/D2172M-17 Method A and ASTM D6307-16 Method A in accordance with Contract Particular Specification issued by Highways Department | | 2112 | | A | A | A | | A |
| BIT 3.17 | Determination of bulk specific gravity of bituminous paving mixtures | ASTM D3203-94 & D3549-93a | | 2122 | | √ | √ | √ | | √ |
| BIT 3.17(a) | Determination of bulk specific gravity and percent air voids in compacted asphalt mixtures | ASTM D3203/D3203M-17 & D3549/D3549M-17 | | 2122 | | A | A | A | | A |
| BIT 3.18(a) | Determination of bulk specific gravity, density and air void content of compacted bituminous paving mixtures using paraffin-coated specimens of 100mm diameter | ASTM D1188-96 & D3203-11 with modification | | 2122 | | √ | √ | √ | | √ |
| BIT 3.18(b) | Determination of bulk specific gravity, density and air void content of compacted bituminous paving mixtures using paraffin-coated specimens of 150mm diameter | ASTM D1188-96 & D3203-11 with modifications | | 2122 | | √ | √ | √ | | √ |
| BIT 3.19 | Determination of air void content of compacted dense and open bituminous paving mixtures | ASTM D3203-11 | | 2122 | | A | A | A | | A |
| BIT 3.20 | Determination of mechanical size analysis of extracted aggregate | ASTM D5444-98 with modifications | | 2112 | | A | A | A | | A |
| BIT 3.20(a) | Determination of mechanical size analysis of extracted aggregate in accordance with ASTM D5444-15 with modifications | ASTM D5444-15 with modifications | | 2112 | | A | A | A | | A |
| BIT 3.21 | Sample preparation from extracted bitumen solution | Appendix AA Clause 9.2.3(i) to (j) of Contract Particular Specification issued by Highways Department | | 2112 | | √ | √ | √ | | √ |
| BIT 3.22 | Recovery of asphalt from solution using the rotary evaporator | ASTM D5404-12 | | 2112 | | √ | | | | √ |
| BIT 3.23 | Determination of bulk specific gravity and density of compacted bituminous mixtures using automatic sealing method | ASTM D6752-11 with modifications | | 2122 | | A | A | A | | A |
| BIT 3.23(a) | Determination of bulk specific gravity, density and percent air voids of compacted asphalt mixtures using automatic sealing method | ASTM D6752/D6752M-18 and D3203/D3203M-17 with modifications | | 2122 | | A | A | A | | A |
| BIT 3.24 | Determination of the absorbance peak height ratio value by the attenuated total reflection (ATR) method using a fourier transform infrared (FTIR) spectrometer | AASHTO T302-15 with modifications | | 2112 | | √ | √ | √ | | √ |
| BIT 4.3 | Determination of surface regularity by rolling straight edge | TRRL Supplementary Report 290 | | 2115 | | √ | √ | √ | | √ |
| BIT 4.5 | Determination of texture depth of carriageways | GS(1992/2006) App. 10.1 | 10.57 | 2115 | | √ | √ | √ | | √ |
| BIT 4.8 | Determination of permeability of friction course | GS(1992/2006) App. 9.1 | 9.62 | 2115 | | √ | √ | √ | | √ |
| BIT 4.9 | Determination of longitudinal and transverse surface regularity of carriageways by 3 meter straightedge | GS(1992/2006) Cl. 10.55(3) | 10.55 | 2115 | | √ | √ | √ | | √ |

Building Blocks, bricks and concrete kerbs

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | | |
|------------|---|---|-----------|--------------------------|-------------------------|----|----|----|----|----|---|
| | | | | | CL | NL | KL | TP | TS | SS | |
| BRK 2.1 | Compressive strength of concrete blocks | BS6073:Part 1:1981 App. B | | 2323 | √ | | | | | | |
| BRK 2.3 | Determination of characteristic compressive strength of interlocking blocks | App. 11.1 of GS 2006 Edition | 11.85 | 2323 | A* | | | | | √ | √ |
| BRK 2.3(a) | Determination of characteristic compressive strength of paving blocks | App. 11.1 of GS 2020 Edition | | 2323 | A* | | | | | | |
| BRK 2.5 | Determination of dimensions and transverse breaking load of clay and calcium silicate pavers for flexible pavements | BS6677:Part 1: 1986 Appendix C and D | | 2323 | √ | | | | √ | | |
| BRK 2.6(b) | Determination of water absorption properties (cold water 24-h immersion test) of masonry units and segmental pavers | AS/NZS 4456.14:1997, AS/NZS 4456.2:1997 and Clause 11.88 (4) of GS 2006 Edition | 11.88(4) | 2323 | A* | | | | √ | | √ |
| BRK 2.6(c) | Determination of water absorption properties (cold water 24-h immersion test) of masonry units and segmental pavers | AS/NZS 4456.14:2003, AS/NZS 4456.2:2003 and Clause 11.88(4) of GS 2020 Edition | 11.88(4) | 2323 | A* | | | | | | |
| BRK 2.7 | Determination of dimensions for precast, unreinforced concrete paving blocks and complementary fittings | BS 6717:2001 Annex B: B1-B3 | | 2323 | A* | | | | | | |
| BRK 2.8 | Determination of dimensions for precast, unreinforced concrete paving flags | BS 7263-1:2001 Annex B: B1-B3 | | 2323 | A* | | | | | | |
| BRK 2.9 | Determination of dimensions and transverse breaking load of clay pavers | Annex B and D of BS EN 1344:2002 | | 2323 | √ | | | | | | |
| BRK 2.10 | Determination of dimensions of concrete paving blocks | BS EN 1338:2003 Annex C.C.1-C.3 | | 2323 | A* | | | | | | |
| BRK 2.11 | Determination of dimensions of concrete paving flags | BS EN 1338:2003 Annex C.C.1-C.3 | | 2323 | A* | | | | | | |
| BRK 2.12 | Determination of dimensions and transverse breaking load of clay pavers | BS EN 1344:2003 Annex B and D | | 2323 | √ | | | | | | |
| BRK 2.13 | Measurement of dimensions and determination of bending strength of precast concrete kerbs | BS EN 1340:2003 Annex C and F | | 2323 | | | | | A | A | |
| BRK 3.2 | Determination of bending strength of precast, unreinforced concrete or artificial granite paving flags | BS 7263-1:2001 Annex E | | 2323 | A* | | | | | | |
| BRK 3.3 | Determination of dimensions for natural/artificial granite paving slabs | BS EN 1341:2001 Annex A: A.1-A.2 & A.4 | | 2323 | √ | | | | | | |
| BRK 3.5 | Determination of bending strength and breaking load of concrete paving flags | BS EN 1339:2003 Annex F | | 2323 | A* | | | | | | |
| BRK 5.1 | Determination of skid resistance value of clay and calcium silicate pavers for flexible pavements | BS6677:Part 1: 1986 | | 2323 | √ | | | | √ | | |
| BRK 5.2 | Determination of unpolished skid resistance value (USRV) of slabs of natural stone for external paving | BS EN 1341:2001 Annex D | | 2323 | A* | | | | | | |
| BRK 5.3 | Determination of the frictional characteristics of new pedestrian surface materials under wet conditions (exclude carpets, ageing or wear testing procedures and in-situ testing) | Appendix A of AS 4586-2013 | | 2323 | √ | | | | | | |
| BRK 5.4 | Determination of unpolished skid resistance value (USRV) of concrete paving blocks | BS EN 1338:2003 Annex I | | 2323 | √ | | | | | | |
| BRK 5.5 | Determination of slip resistance value (SRV) of sets of natural stone for external paving in wet test condition | BS EN 14231:2003 Cl. 8.3 in conjunction with BS EN 1342:2012 Cl. 4.6.1 | | 2323 | √ | | | | | | |
| BRK 5.5(a) | Determination of unpolished skid resistance value (USRV) of sets of natural stone for external paving | BS EN 1342:2001 Annex C | | 2323 | A* | | | | | | |
| BRK 5.6 | Determination of unpolished slip/skid resistance value (USRV) of clay pavers | CEN/TS 16165:2012 Annex C in conjunction with BS EN 1344:2013 Cl. 4.2.5 | | 2323 | √ | | | | | | |
| BRK 5.6(a) | Determination of unpolished skid resistance value (USRV) of clay pavers | BS EN 1344:2002 Annex F | | 2323 | A* | | | | | | |

Calibration

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | | |
|-------------|--|---|-----------|--------------------------|-------------------------|----|----|----|----|----|--|
| | | | | | CL | NL | KL | TP | TS | SS | |
| CAL 1.1 | Verification of the grading of forces applied by uniaxial/universal/compression testing machines | BS1610:Part 1:1985 | | | A | | | | | | |
| CAL 1.1(a) | Load verification of uniaxial testing machine, using true/indicated force method, in compression/tension | BS EN ISO 7500-1:1999 BS EN ISO 7500-1:2004 | | | A | | | | | | |
| CAL 1.1(b) | Load verification of tensile testing machine, using true/indicated force method | BS EN 10002-2:1992 | | | A | | | | | | |
| CAL 1.1(c) | Verification of the forces measuring system of the tension/compression testing machines | BS EN ISO 7500-1:2018 | | | A | | | | | | |
| CAL 1.3 | Performance verification of concrete compression machines by footometer | BS1881:Part 1 15:1986 App. A/ CSI:1990 App. D BS EN 12390-4:2000 App.A/ CSI:2010 App.D | | | A | | | | | | |
| CAL 1.5 | Verification of the grading of forces applied by uniaxial compression testing machines | BS1610:Part 1:1992 | | | A | | | | | | |
| CAL 1.5(a) | Verification of the forces measuring system of the compression testing machines | Annex B of BS EN 12390-4:2000 | | | A | | | | | | |
| CAL 1.6 | Calibration of force measuring device | GEOSPEC 3 Cl. A3 | | | A | | | | | | |
| CAL 1.10 | Calibration of force measuring device (load cell) | In-house test method | | | A | | | | | | |
| CAL 2.2 | Calibration of pressure or vacuum gauges | In-house test method based on BS EN837-1:1998 CL. 6, 9.1, 9.2 and 10.2 | | | A | | | | | | |
| CAL 2.4 | Calibration of pressure measuring device | GEOSPEC 3 Cl. A3.2 | | | A | | | | | | |
| CAL 3.1 (a) | Calibration of extensometer | BS3846:1970 | | | A | | | | | | |
| CAL 3.1 (b) | Calibration of circumferential extensometer | BS3846:1970 | | | A | | | | | | |
| CAL 3.1 (f) | Calibration of extensometer | BSEN 10002-4:1995/BSEN ISO 9513 : 2002 | | | A | | | | | | |
| CAL 3.1 (g) | Calibration of extensometer in accordance with BS EN ISO 9513 : 2012 | BS EN ISO 9513:2012 | | | A | | | | | | |
| CAL 3.2 | Calibration of calipers | In-house test method | | | A | | | | | | |
| CAL 3.3 | Calibration of external micrometers | In-house test method | | | A | | | | | | |
| CAL 3.4 | Calibration of dial gauges | In-house test method | | | A | | | | | | |
| CAL 3.5 | Calibration of length measuring devices | In-house test method | | | A | | | | | | |
| CAL 3.5(a) | Calibration of 3-Dimensional length measuring device | In-house test method | | | √ | | | | | | |
| CAL 3.9 | Calibration of lever system for the consolidation apparatus and direct shear apparatus | In-house test method | | | √ | | | | | | |
| CAL 3.11 | Calibration of depth gauge | In-house test method | | | √ | | | | | | |
| CAL 3.12 | Calibration of scale rule | In-house test method | | | √ | | | | | | |
| CAL 3.13 | Calibration of feeler gauge | In-house test method | | | √ | | | | | | |
| CAL 3.14 | Calibration of measuring tape | In-house test method | | | √ | | | | | | |
| CAL 3.15 | Calibration of engineers' square | In-house test method based on 10.1, 10.2, 10.3, 10.4 & 10.8 of BS 939:1977 | | | √ | | | | | | |
| CAL 4.5 | Calibration of flatness and parallelism of platen surface | In-house test method | | | √ | | | | | | |
| CAL 4.7 | Calibration of skid resistance tester | BS EN 1097-8:2000 | | | A | | | | | | |
| CAL 4.7(a) | Calibration of skid resistance tester | BS EN 14231:2003 / BS EN 1338:2003 | | | √ | | | | | | |
| CAL 4.7(b) | Calibration of skid resistance tester | CEN/TS 16165:2012 | | | √ | | | | | | |
| CAL 6.1 | Calibration of thermometers | In-house test method | | | A | | | | | | |
| CAL 6.2 | Verification of temperature range of constant temperature enclosures | In-house test method | | | √ | | | | | | |
| CAL 6.4 | Calibration of high temperature enclosures | In-house test method | | | √ | | | | | | |
| CAL 6.5 | Verification of infrared oven | In-house test method | | | √ | | | | | | |
| CAL 10.2 | Calibration of masses | In-house test method | | | A | | | | | | |
| CAL 10.3 | Calibration of balances of capacity over 30 kg | In-house test method | | | √ | | | | | | |
| CAL 10.4 | Calibration of balance | In-house test method | | | A | | | | | | |
| CAL 20.1 | Calibration of automatic volume change apparatus | Part II of Geospec: 3 | | | √ | | | | | | |

Cement

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | |
|-----------|--|--------------------------------|-----------|--------------------------|-------------------------|----|----|----|----|----|
| | | | | | CL | NL | KL | TP | TS | SS |
| CEM 0.0 | Sample receipt for cement | In-house procedure | | | √ | | | | | |
| CEM 1.6 | Tests for cement setting times | BS EN 196-3:1995 Cl. 6 | | 2322 | A* | | | | | |
| CEM 1.7 | Determination of cement standard consistence | BS EN 196-3:1995 Cl. 5 | | 2322 | A* | | | | | |
| CEM 1.8 | Cement soundness test | BS EN 196-3:1995 Cl. 7 | | 2322 | A* | | | | | |
| CEM 1.9 | Cement density test | BS EN 196-6: 1992 Annex NC | | 2322 | A* | | | | | |
| CEM 1.10 | Cement fineness test by blaine method | BS EN 196-6: 1992 Cl. 4 | | 2322 | A* | | | | | |
| CEM 1.11 | Test for cement setting times | BS EN 196-3:2005+A1:2008 Cl. 6 | | 2322 | A* | | | | | |
| CEM 1.12 | Determination of cement standard consistence | BS EN 196-3:2005+A1:2008 Cl. 5 | | 2322 | A* | | | | | |
| CEM 1.13 | Cement soundness test | BS EN 196-3:2005+A1:2008 Cl. 7 | | 2322 | A* | | | | | |
| CEM 1.14 | Cement density test | BS EN 196-6: 2010 Annex NC | | 2322 | A* | | | | | |
| CEM 1.15 | Cement fineness test by blaine method | BS EN 196-6: 2010 Cl. 4 | | 2322 | A* | | | | | |
| CEM 2.3 | Determination of cement strength by flexural and compressive strength tests on prismatic specimens | BS EN 196-1:1995 | | 2322 | A* | | | | | |
| CEM 2.4 | Determination of cement strength by flexural and compressive strength tests on prismatic specimens | BS EN 196-1:2005 | | 2322 | A* | | | | | |

Chemical

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | |
|------------|---|---|---------------|--------------------------|-------------------------|----|----|----|----|----|
| | | | | | CL | NL | KL | TP | TS | SS |
| CHM 0.0 | Quality control manual for chemical testing unit | Quality manual | | | √ | | | | | |
| CHM 0.1 | Miscellaneous work instructions for chemical testing unit | Quality manual | | | √ | | | | | |
| CHM 1.1 | Determination of chloride content of admixture | BSS075:Part 1: 1982 Appendix E | 16.10 & 16.51 | 2203 | A | | | | | |
| CHM 2.6 | Determination of water-soluble chloride content of aggregates | CS3:2013, Section 21.3 | | 2204 | A | | | | | |
| CHM 2.7 | Determination of acid-soluble sulphate content of aggregates | CS3:2013, Section 21.5 | | 2204 | A | | | | | |
| CHM 2.8 | Determination of total sulphur content of aggregates | CS3:2013, Section 21.6 | | 2204 | A | | | | | |
| CHM 2.9 | Determination of presence of humus | CS3:2013, Section 21.7 | | 2204 | A | | | | | |
| CHM 4.5 | Determination of loss-on-ignition of cement | BS EN 196-2:2005, Cl. 7 | | 2205 | A | | | | | |
| CHM 4.6 | Determination of sulphate content of cement | BS EN 196-2:2005, Cl. 4.4.1 | | 2205 | √ | | | | | |
| | | BS EN 196-2:2005, Cl. 8 | | 2205 | A | | | | | |
| CHM 4.7 | Determination of residue insoluble in hydrochloric acid and sodium carbonate in cement | BS EN 196-2:2005, Cl. 4.4.2 | | 2205 | √ | | | | | |
| | | BS EN 196-2:2005, Cl. 9 | | 2205 | A | | | | | |
| CHM 4.8 | Determination of chloride content of cement | BS EN 196-2:2005, Cl. 14 | | 2205 | √ | | | | | |
| | | BS EN 196-2:2005, Cl. 4.3 | | 2205 | A | | | | | |
| CHM 4.8 | Determination of chloride content of cement | BS EN 196-2:2005, Cl. 14 | | 2205 | √ | | | | | |
| | | BS EN 196-2:2005, Cl. 4.5.16 | | 2205 | A | | | | | |
| CHM 4.10 | Determination of total alkali content of cement | BS EN 196-2:2005, Cl.17 | | 2205 | √ | | | | | |
| | | BS EN 196-2:2005, Cl.17 | | 2205 | A | | | | | |
| CHM 4.11 | Determination of iron (III) oxide and aluminium oxide content of cement | BS EN 196-2:2005, Cl.13.2, Cl.13.4, Cl.13.6.1, Cl.13.7, Cl.13.10 and Cl.13.11 | | 2205 | √ | | | | | |
| | | BS EN 196-2:2005, Cl.13.2, Cl.13.4, Cl.13.6.1, Cl.13.7, Cl.13.10 and Cl.13.11 | | 2205 | A | | | | | |
| CHM 5.3 | Determination of chloride content in hardened concrete | CS1:2010 and CS1:1990 Section 21.10.2 and BS1881:Part14:1988 | | 2206 | A | | | | | |
| CHM 5.4 | Determination of sulphate content in hardened concrete | CS1:2010 Section 21.10.3 and CS1:1990 Section 21.10.3 | | 2206 | A | | | | | |
| CHM 5.8 | Determination of cement content and aggregate content of hardened concrete | CS1:2010 and CS1:1990, section 21.6 | | 2206 | √ | | | | | |
| CHM 5.9 | Determination of carbonation depth in hardened concrete by the phenolphthalein method | BS EN 14630: 2006 | | 2206 | √ | | | | | |
| CHM 6.5 | Determination of total alkali content of pulverized-fuel ash | BS EN 196-2:2005, Cl.17 | | 2207 | A | | | | | |
| CHM 6.7 | Determination of moisture content of pulverized-fuel ash | BS 3892: Part 1:1997 (Annex C) | | 2207 | A | | | | | |
| CHM 6.8 | Determination of loss-on-ignition of pulverized-fuel ash | BS EN 196-2:2005, Cl.7 | | 2207 | √ | | | | | |
| | | BS EN 196-2:2005, Cl.7 | | 2207 | A | | | | | |
| CHM 6.9 | Determination of sulphuric anhydride content of pulverized-fuel ash | BS EN 196-2:2005, Cl. 8 | | 2207 | A | | | | | |
| CHM 6.10 | Determination of chloride content of pulverized-fuel ash | BS EN 196-2:2005, Cl.14 | | 2207 | A | | | | | |
| CHM 6.11 | Determination of calcium oxide content of pulverized-fuel ash | BS EN 196-2:2005, Cl.13 | | 2207 | A | | | | | |
| CHM 7.1 | Determination of total sulphate content of soil and sulphate content of groundwater and aqueous soil extracts by gravimetric method | Geospec 3, Cl. 9.3 | 6.59 | 2208 | A | | | | | |
| CHM 7.2 | Determination of water soluble chloride content of soil | Geospec 3, Cl. 9.4 | | 2208 | A | | | | | |
| CHM 7.3 | Determination of pH value of soil and groundwater | Geospec 3, Cl. 9.5 | | 2208 | A | | | | | |
| CHM 7.4 | Determination of organic matter content of soil | Geospec 3, Cl. 9.1 | | 2208 | A | | | | | |
| CHM 7.6 | Determination of the mass loss of soil on ignition | Geospec 3, Cl. 9.2 | | 2208 | A | | | | | |
| CHM 8.3(b) | Gravimetric determination of the mass per unit area of hot dip galvanized coatings on steel wires | BS EN ISO 1460: 1995 | | 2210 | √ | | | | | |
| CHM 8.4 | Determination of carbon, sulphur, phosphorus, nitrogen, copper, manganese, chromium, molybdenum, vanadium and nickel content of steel by spark spectrometry | In-house test method | | 2209 | A | | | | | |
| CHM 8.5 | Determination of nitrogen content of steel | BS EN ISO 15351: 2010 | | 2209 | A | | | | | |
| CHM 8.6 | Determination of total carbon and sulphur content of steel by infrared absorption method after combustion in an induction furnace | In-house test method | | 2209 | A | | | | | |
| CHM 8.7 | Determination of zinc and zinc alloy coatings of steel wire | BS EN 10244-2: 2009 | | 2210 | √ | | | | | |
| CHM 9.8 | Determination of chloride in water | APHA 21 st Edition (2005) - Part 4500 - Cl ⁻ Section B | | 2211 | √ | | | | | |
| CHM 11.4 | Determination of moisture content of ground granulated blast furnace slag | BS EN 15167-1: 2006 (Annex A) | | 2212 | √ | | | | | |
| CHM 11.5 | Determination of chloride content of ground granulated blast furnace slag | BS EN 196-2:2005, Cl. 14 | | 2212 | √ | | | | | |
| CHM 11.6 | Determination of sulphate content of ground granulated blast furnace slag | BS EN 196-2:2005, Cl. 8 | | 2212 | √ | | | | | |
| CHM 11.7 | Determination of loss-on-ignition of ground granulated blast furnace slag | BS EN 196-2:2005, Cl. 7 | | 2212 | √ | | | | | |
| CHM 11.8 | Determination of magnesium oxide content of ground granulated blastfurnace slag | BS EN 196-2:2005, Cl.13.13 | | 2212 | √ | | | | | |
| CHM 11.9 | Determination of sulphide content of ground granulated blastfurnace slag | BS EN 196-2:2005, Cl.11 | | 2212 | √ | | | | | |
| CHM 15.1 | Determination of organic matter content of glass cullet | Geospec 3, Cl. 9.1 | | 2213 | √ | | | | | |

Concrete

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | |
|-------------|--|--|-----------|--------------------------|-------------------------|----|----|----|----|----|
| | | | | | CL | NL | KL | TP | TS | SS |
| CON 2.6 | Measurement of dimensions & determination of transverse strength of precast concrete kerbs | BS7263:Part 1:1994 Annex A and Annex B | 11.51 | 2324 | A* | | | √ | √ | |
| CON 2.9 | Compression test of concrete cubes and cement grout cubes | CS1:2010 Section 10, 12 & 16 | 16.58 | 2309 | A | A | A | A | A | A |
| CON 2.10(a) | Compressive strength of concrete cores to CS1:2010 (for 100 mm diameter size) | CS1:2010 Section 15 | 16.63 | 2313 | A | | A | A | A | A |
| CON 2.10(b) | Compressive strength of concrete cores to CS1:2010 (for 150 mm diameter size) | CS1:2010 Section 15 | 16.63 | 2313 | A | | A | A | A | A |
| CON 2.11 | Determination of tensile splitting strength of cylindrical concrete | CS1:2010, Vol. 2:Section 13 | | 2324 | A | | | | A | A |
| CON 2.12 | Determination of flexural strength of concrete beams | CS1:2010:Section 14 | | 2324 | A* | | | | | |
| CON 5.8 | Determination of water absorption of concrete | BS1881:Part 122:1983 | | 2324 | √ | | | √ | √ | |
| CON 5.12 | Determination of concrete's ability to resist chloride ion penetration | CS1:2010, V2, Sect 19 | | 2324 | A* | | | | | |
| CON 5.15 | Determination of the bending strength of wall panels | BS4225:2008:2:2009 | | 2324 | √ | | | | | |
| CON 6.5 | Surface hardness testing by rebound hammer | BS1881:Part 202:1986 | | 2324 | | | √ | | √ | |
| CON 6.5(a) | Determination of rebound number of an area of hardened concrete using a spring-driven hammer | BS EN 12504-2:2021 | | 2324 | | | √ | | √ | √ |

Geotextile

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | |
|-----------|--|---------------|-----------|--------------------------|-------------------------|----|----|----|----|----|
| | | | | | CL | NL | KL | TP | TS | SS |
| GTL 2.1 | Determination of tensile properties of geotextile by the wide-width strip method | ASTM D4595-86 | | 2404 | √ | | | | | |

Ground Granulated Blast Furnace Slag

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | |
|-----------|--|---|-----------|--------------------------|-------------------------|----|----|----|----|----|
| | | | | | CL | NL | KL | TP | TS | SS |
| GGB 0.0 | Sample receipt of GGBS | In-house procedure | | | √ | | | | | |
| GGB 1.1 | Determination of activity index | BS EN 196-1:1995 Cl. 9.3 in conjunction with BS EN 15167-1:2006 Cl. 5.3.2.3 | | 2326 | A ⁺ | | | | | |
| GGB 1.2 | Determination of standard consistence | BS EN 196-3:1995 Cl. 5 in conjunction with BS EN 15167-1:2006 Cl. 5.3.2.2 | | 2326 | A ⁺ | | | | | |
| GGB 1.3 | Determination of initial setting time | BS EN 196-3:1995 Cl. 6.1 and 6.2 in conjunction with BS EN 15167-1:2006 Cl. 5.3.2.2 | | 2326 | A ⁺ | | | | | |
| GGB 1.4 | Determination of particle density | BS EN 196-6:1992 Annex NC in conjunction with BS EN 15167-1:2006 Cl. 5.5g | | 2326 | A ⁺ | | | | | |
| GGB 1.5 | Fineness test by blaine method | BS EN 196-6:1992 Cl. 4 in conjunction with BS EN 15167-1:2006 Cl. 5.3.1 | | 2326 | A ⁺ | | | | | |
| GGB 1.6 | Determination of activity index of ground granulated blast furnace slag (GGBS) | BS EN 196-1:2005 Cl. 9.2 in conjunction with BS EN 15167-1:2006 Cl. 5.3.2.3 | | 2326 | A ⁺ | | | | | |
| GGB 1.7 | Determination of standard consistence for ground granulated blast furnace slag (GGBS) | BS EN 196-3:2005+A1:2008 Cl. 5 in conjunction with BS EN 15167-1:2006 Cl. 5.3.2.2 | | 2326 | A ⁺ | | | | | |
| GGB 1.8 | Determination of initial setting time of ground granulated blast furnace slag (GGBS) | BS EN 196-3:2005+A1:2008 Cl. 6.1 and 6.2 in conjunction with BS EN 15167-1:2006 Cl. 5.3.2.2 | | 2326 | A ⁺ | | | | | |
| GGB 1.9 | Determination of particle density for ground granulated blast furnace slag (GGBS) for use with portland cement | BS EN 196-6:2010 Annex NC in conjunction with BS EN 15167-1:2006 Cl. 5.5g | | 2326 | A ⁺ | | | | | |
| GGB 1.10 | Ground granulated blast furnace slag (GGBS) fineness test by blaine method | BS EN 196-6:2010 Cl. 4 in conjunction with BS EN 15167-1:2006 Cl. 5.3.1 | | 2326 | A ⁺ | | | | | |

Miscellaneous tests

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | |
|------------|--|--|-----------|--------------------------|-------------------------|----|----|----|----|----|
| | | | | | CL | NL | KL | TP | TS | SS |
| MIS 2.1 | Determination of skid resistance value of road surface in accordance with guidance notes on road testing (RDGN/009) issued by highways department | Guidance Notes on Road Testing (RDGN/009) | | 2115 | | | √ | √ | √ | |
| MIS 4.1 | Determination of extrusion of joint filler | GS(2006) with amendment 2/2013 | | 2417 | √ | | | | | |
| MIS 4.2 | Weathering test of joint filler | In-house method | | 2417 | √ | | | | | |
| MIS 4.3 | Determination of the recovery value and reduction of joint filler | GS(2006) with amendment 2/2013 | | 2417 | √ | | | | | |
| MIS 5.1 | Determination of length of installed steel soil nail, steel bar anchor or steel wire rope anchor with a pre-installed wire by the use of time domain reflectometry (TDR) cable fault locator | In-house method | | | √ | | | | | |
| MIS 6.1 | Determination of head injury criterion value for impact absorbing playground surfacing | BS EN 1177:1998 | | | A | | | | | |
| MIS 7.1 | Measurement of coating thickness by magnetic method | BS EN ISO 2178: 1995 | | 2411 | | | √ | √ | √ | |
| MIS 7.1(a) | Measurement of coating thickness by magnetic method | BS EN ISO 2178: 2016 in conjunction with BS EN ISO 1461:2009 | | 2428 | | | A | A | A | |
| MIS 10.1 | Unconfined compression test of cement soil cores | Interim Guidelines on Testing of Unconfined Compressive Strength of Cement Stabilised Soil Cores in Hong Kong (October 2017, HKIE) | | 2601 | A | | | | | |
| MIS 11.1 | Determination of moisture content of glass cullet by oven-drying at 105°C ± 5°C | Geospec 3 - Test Method 5.2 with modification | | | √ | | | | | |
| MIS 11.2 | Determination of particle size distribution of glass cullet by wet sieving (without dispersant) | Geospec 3 - Test Method 8.2 with modification | | | √ | | | | | |

PFA

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | |
|-----------|--|---|-----------|--------------------------|-------------------------|----|----|----|----|----|
| | | | | | CL | NL | KL | TP | TS | SS |
| PFA 0.0 | Sample receipt for pulverised-fuel ash (PFA) | In-house procedure | | | √ | | | | | |
| PFA 1.3 | Determination of fineness of pulverised-fuel ash (PFA) | BS 3892 : Part 1 : 1997 Annex D | | 2325 | A ⁺ | | | | | |
| PFA 1.4 | Determination of water requirement of pulverised-fuel ash (PFA) | BS 3892 : Part 1 : 1997 Annex E | | 2325 | A ⁺ | | | | | |
| PFA 1.5 | Determination of particle density of pulverised-fuel ash (PFA) | BS 3892 : Part 1 : 1997 Clause 7 | | 2325 | A ⁺ | | | | | |
| PFA 1.6 | Determination of initial setting times of pulverised-fuel ash (PFA) | BS 3892 : Part 1 : 1997 Clause 10 | | 2325 | A ⁺ | | | | | |
| PFA 1.7 | Determination of standard consistence of pulverised-fuel ash (PFA) | BS 3892 : Part 1 : 1997 Clause 10 | | 2325 | A ⁺ | | | | | |
| PFA 1.8 | Determination of soundness of pulverised-fuel ash (PFA) | BS 3892 : Part 1 : 1997 Clause 11 | | 2325 | A ⁺ | | | | | |
| PFA 1.9 | Determination of strength factor of pulverised-fuel ash (PFA) | BS 3892 : Part 1 : 1997 Annex F | | 2325 | A ⁺ | | | | | |
| PFA 1.10 | Determination of fineness of pulverised-fuel ash (PFA) | BS EN 451-2:2017 in conjunction with BS EN 450-1:2012 Cl. 5.3.1 | | 2325 | √ | | | | | |
| PFA 1.11 | Determination of water requirement of pulverised-fuel ash (PFA) for use with Portland cement | BS EN 450-1:2012 Annex B in conjunction with BS EN 450-1:2012 Cl. 5.3.6 | | 2325 | √ | | | | | |
| PFA 1.12 | Determination of particle density of pulverised-fuel ash (PFA) | BS EN 1097-7:2008 in conjunction with BS EN 450-1:2012 Cl. 5.3.4 with modification | | 2325 | √ | | | | | |
| PFA 1.13 | Determination of initial setting times of pulverised-fuel ash (PFA) for use with Portland cement | BS EN 196-3:2005+A1:2008 Cl. 6.1 and 6.2 in conjunction with BS EN 450-1:2012 Cl. 5.3.5 | | 2325 | √ | | | | | |
| PFA 1.14 | Determination of standard consistence of pulverised-fuel ash (PFA) for use with Portland cement | BS EN 196-3:2005+A1:2008 Cl. 5 in conjunction with BS EN 450-1:2012 Cl. 5.3.5 | | 2325 | √ | | | | | |
| PFA 1.15 | Determination of soundness of pulverised-fuel ash (PFA) for use with Portland cement | BS EN 196-3:2005+A1:2008 Cl. 7 in conjunction with BS EN 450-1:2012 Cl. 5.3.3 | | 2325 | √ | | | | | |
| PFA 1.16 | Determination of activity index of pulverised-fuel ash (PFA) for use with Portland cement | BS EN 196-1:2005 Cl. 9 in conjunction with BS EN 450-1:2012 Cl. 5.3.2 | | 2325 | √ | | | | | |

Pipes

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | |
|------------|---|--|-----------|--------------------------|-------------------------|----|----|----|----|----|
| | | | | | CL | NL | KL | TP | TS | SS |
| PIP 1.1(b) | Water absorption of vitrified clay pipe | BS 65:1991 Cl. F.1 and F.2 in conjunction with BS 65:1991 Cl. 6.6.1 | 5.82 | 2427 | A ⁺ | | | | | |
| PIP 1.1(d) | Determination of water absorption of precast concrete street gullies / inspection chambers and watertightness of precast concrete street gullies | BS5911: Part 2:1982 with Amendment No. 1 | | 2427 | A ⁺ | | | | | |
| PIP 1.4 | Heat reversion test for unplasticized polyvinyl chloride (PVC) pipes (up to 16" nominal size) | BS 3506:1969 App. A in conjunction with BS 3506:1969 Cl. 8.2 | | 2427 | A ⁺ | | | | | |
| PIP 1.5 | Determination of water absorption of precast concrete pipes and fittings | BS EN 1916:2002 Annex F in conjunction with BS EN 1916:2002 Cl. 4.2.6.2 | | 2427 | A ⁺ | | | | | |
| PIP 1.6 | Heat reversion test for unplasticized PVC soil and ventilating pipes | BS 2782-11:Method 1102B:1981 in conjunction with BS 4514:1983 Cl. 5.4 | | 2427 | A ⁺ | | | | | |
| PIP 1.7 | Heat reversion test for unplasticized polyvinyl chloride (PVC-U) pipes for below ground gravity drainage and sewerage | BS 2782-11:Method 1102B:1981 in conjunction with BS 4660:1989 Cl. 6.4 | | 2427 | A ⁺ | | | | | |
| PIP 1.8 | Heat reversion test for unplasticized PVC pipes for gravity sewers (up to 400 mm nominal size) | BS 5481:1977 App. A in conjunction with BS 5481:1977 Cl. 8.1.4 | | 2427 | A ⁺ | | | | | |
| PIP 1.9 | Determination of Longitudinal Reversion for Unplasticized Poly(Vinyl Chloride) (PVC-U) Pipes (up to the Nominal Outside Diameter of 400 mm) | EN ISO 2505:2005 (by Air Oven) in conjunction with BS EN 1401-1:2009 Cl. 8.1 | | 2427 | √ | | | | | |
| PIP 1.10 | Determination of Longitudinal Reversion for Unplasticized Poly(Vinyl Chloride) (PVC-U) Pipes | EN 743:1994 (Method B) in conjunction with BS EN 12200-1:2000 Cl. 8.1 | | 2427 | √ | | | | | |
| PIP 2.1(b) | Crushing strength test on vitrified clay pipe | BS65:1991 | 5.82 | 2427 | √ | | | | | |
| PIP 2.1(c) | Determination of crushing strength of vitrified clay pipe | BS EN 295-Part 3:1991 | | 2427 | √ | | | | | |
| PIP 2.1(f) | Determination of crushing strength of vitrified clay pipes (up to 900 mm nominal size) | BS EN 295-3:2012 Cl. 7 in conjunction with BS EN 295-1:2013 Cl. 5.9 | | 2427 | A ⁺ | | | | | |
| PIP 2.2 | Impact Strength Test for unplasticized PVC Pipes for Industrial Uses (from 2" to 16" nominal size) | BS 3506:1969 App. E in conjunction with BS 3506:1969 Cl. 9.2 | 5.82 | 2427 | A ⁺ | | | | | |
| PIP 2.4 | Determination of crushing strength of precast concrete pipes and fittings (up to 900 mm diameter) | BS EN 1916:2002 Annex C in conjunction with BS 5911-1:2002+A2:2010 Cl. 5.6 | | 2427 | A ⁺ | | | | | |
| PIP 2.5 | Impact resistance test for unplasticized PVC soil and ventilating pipes | BS 4514:1983 App. B in conjunction with BS 4514:1983 Cl. 5.3 | | 2427 | A ⁺ | | | | | |
| PIP 2.6 | Impact resistance test for unplasticized polyvinyl chloride (PVC-U) pipes for below ground gravity drainage and sewerage | BS 2782-11:Method 1108A:1989 in conjunction with BS 4660:1989 Cl. 6.3 | | 2427 | A ⁺ | | | | | |
| PIP 2.7 | Impact resistance test for the unplasticized PVC pipes for gravity sewers (up to 400 mm nominal size) | BS 5481:1977 App. G in conjunction with BS 5481:1977 Cl. 8.1.3 | | 2427 | A ⁺ | | | | | |
| PIP 2.8 | Determination of Impact Resistance (Round-the-Clock Method) for Unplasticized Poly(Vinyl Chloride) (PVC-U) Pipes (up to the Nominal Outside Diameter of 400 mm) | EN 744:1995 in conjunction with BS EN 1401-1:2009 Cl. 7.1.1 | | 2427 | √ | | | | | |
| PIP 2.9 | Determination of Impact Resistance (Round-the-Clock Method) for Unplasticized Poly(Vinyl Chloride) (PVC-U) Pipes | EN 744:1995 in conjunction with BS EN 12200-1:2000 Cl. 7.1 | | 2427 | √ | | | | | |

Rock

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | |
|------------|--|---|-----------|--------------------------|-------------------------|----|----|----|----|----|
| | | | | | CL | NL | KL | TP | TS | SS |
| ROC 1.1(a) | Preparation of thin sections (28 mm x 48 mm) | In-house test method | | | √ | | | | | |
| ROC 1.2 | Preparation of rock core specimens and determination of dimensional and shape tolerances | ASTM D4543-91 with modifications | | | A | | | | | |
| ROC 2.1 | Determination of water content | ASTM D2216-98 | | | √ | | | | | |
| ROC 2.2 | Determination of porosity/density using saturation and caliper techniques | ISRM suggested method (1981) with modifications | | | √ | | | | | |
| ROC 2.8 | Determination of point load strength for diametral and axial tests | ASTM D5731-95 | | 2513 | A | | | | | |
| ROC 2.9 | Determination of cerchar abrasiveness index (CAI) | ASTM D7625-10 (2010) | | | A | | | | | |
| ROC 3.2 | Determination of unconfined uniaxial compressive strength | ASTM D2938-95 | | 2513 | A | | | | | |
| ROC 3.5 | Determination of elastic moduli in uniaxial compressive test | ASTM D3148-06 | | 2513 | A | | | | | |
| ROC 3.6 | Determination of direct shear strength of rock discontinuities under constant normal force | ASTM D5607-95 with modifications | | | A | | | | | |

Rubber compounds

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | |
|------------|---|---|-----------|--------------------------|-------------------------|----|----|----|----|----|
| | | | | | CL | NL | KL | TP | TS | SS |
| RUB 1.3 | Determination of density of non-cellular plastics | Method 620A of BS2782-Part 6:1991/ISO 1183:1987 | | 2424 | √ | | | | | |
| RUB 1.3(a) | Determination of density of non-cellular plastics by immersion method | BS EN ISO 1183-1:2012 Cl. 5.1 with modification | | 2424 | √ | | | | | |
| RUB 2.1 | Hardness (IRHD) test | BS903:Part A26:1995 | 16.91 | 2424 | √ | | | | | |
| RUB 5.1 | Determination of flexural properties of plastic fender | Appendix 21.1 of GS 2006 | | 2424 | √ | | | | | |

Soils

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | |
|------------|---|---|-----------|--------------------------|-------------------------|----|----|----|----|----|
| | | | | | CL | NL | KL | TP | TS | SS |
| SOL 1.1(b) | Procedures for the longitudinal splitting of macier sample tube | In-house method | | | √ | | | | | |
| SOL 2.18 | Determination of soil moisture content by infrared oven drying | In-house method | | 2510 | A | A | A | A | A | A |
| SOL 8.4 | Determination of in-situ california bearing ratio (CBR) | BS 1377: Part 9:1990 Method 4.3 with modification | | 2511 | | | √ | √ | √ | √ |
| SOL 8.7 | Determination of penetration resistance of soil using dynamic probe (GEO Probe) | GS(2006) App. 7.1 | | 2511 | | | | √ | √ | |

Soils - Geospec

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | |
|-------------|--|---|------------|--------------------------|-------------------------|----------------|----------------|----------------|----------------|----------------|
| | | | | | CL | NL | KL | TP | TS | SS |
| GSP 5.1 | Determination of moisture content by oven-drying at 45°C ± 5°C | Geospec 3 - Test Method 5.1 | 6.65 | 2510 | A | A | A | A | A | A |
| GSP 5.2 | Determination of moisture content by oven-drying at 105°C ± 5°C | Geospec 3 - Test Method 5.2 | 6.65 | 2510 | A | A | A | A | A | A |
| GSP 5.3 | Comparative test for determination of moisture content by oven-drying | Geospec 3 - Test Method 5.3 | | 2510 | A | A | A | A | A | A |
| GSP 6.1 | Determination of liquid limit, plastic limit and plasticity index | Geospec 3 - Test Method 6.1 | 6.59 | 2510 | A | A | A | A | A | A |
| GSP 6.2 | Determination of liquidity index | Geospec 3 - Test Method 6.2 | | 2510 | A | A | A | A | A | A |
| GSP 7.1 | Determination of particle density by gas jar method | Geospec 3 - Test Method 7.1 | | | A | √ | √ | √ | √ | √ |
| GSP 7.2 | Determination of particle density by small pycnometer | Geospec 3 - Test Method 7.2 | | | A | √ | √ | √ | √ | √ |
| GSP 8.1 | Determination of particle size distribution by wet sieving (with dispersant) | Geospec 3 - Test Method 8.1 | 6.59 | 2510 | A | A | A | A | A | A |
| GSP 8.2 | Determination of particle size distribution by wet sieving (without dispersant) | Geospec 3 - Test Method 8.2 | 6.59 | 2510 | A | A | A | A | A | A |
| GSP 8.5 | Determination of particle size distribution by hydrometer (with dispersant) | Geospec 3 - Test Method 8.5 | | 2510 | A | A | A | A | A | A |
| GSP 8.6 | Determination of particle size distribution by hydrometer (without dispersant) | Geospec 3 - Test Method 8.6 | | 2510 | A | A | A | A | A | A |
| GSP 8.7 | Construction of a continuous particle size distribution curve | Geospec 3 - Test Method 8.7 | | 2510 | A | A | A | A | A | A |
| GSP 8.8 | Determination of particle size distribution of fill material | Geospec 3 - Test Method 8.18.2 | 6.72(3) | 2510 | A | A | A | A | A | A |
| GSP 10.1 | Determination of dry density/moisture content relationship of soils containing particles which are not susceptible to crushing (1000kc mould and 2.5kg rammer) | Geospec 3 - Test Method 10.1 | 6.62 | 2510 / 2511 | A | A | A | A | A | A |
| GSP 10.2 | Determination of dry density/moisture content relationship of soils containing particles which are susceptible to crushing (1000kc mould and 2.5kg rammer) | Geospec 3 - Test Method 10.2 | 6.62 | 2510 / 2511 | A | A | A | A | A | A |
| GSP 10.3 | Determination of dry density/moisture content relationship of soils containing particles which are not susceptible to crushing (CBR mould and 2.5kg rammer) | Geospec 3 - Test Method 10.3 | 6.62 | 2510 / 2511 | A | A | A | A | A | A |
| GSP 10.4 | Determination of dry density/moisture content relationship of soils containing particles which are susceptible to crushing (CBR mould and 2.5kg rammer) | Geospec 3 - Test Method 10.4 | 6.62 | 2510 / 2511 | A | A | A | A | A | A |
| GSP 10.5 | Determination of dry density/moisture content relationship of soils containing particles which are not susceptible to crushing (1000kc mould and 4.5kg rammer) | Geospec 3 - Test Method 10.5 | 6.62 | 2510 / 2511 | A | A | A | A | A | A |
| GSP 10.6 | Determination of dry density/moisture content relationship of soils containing particles which are susceptible to crushing (1000kc mould and 4.5kg rammer) | Geospec 3 - Test Method 10.6 | 6.62 | 2510 / 2511 | A | A | A | A | A | A |
| GSP 10.7 | Determination of dry density/moisture content relationship of soils containing particles which are not susceptible to crushing (CBR mould and 4.5kg rammer) | Geospec 3 - Test Method 10.7 | 6.62 | 2510 / 2511 | A | A | A | A | A | A |
| GSP 10.8 | Determination of dry density/moisture content relationship of soils containing particles which are susceptible to crushing (CBR mould and 4.5kg rammer) | Geospec 3 - Test Method 10.8 | 6.62 | 2510 / 2511 | A | A | A | A | A | A |
| GSP 11.1 | Determination of in-situ bulk density and in-situ dry density of soils by the sand replacement method (with small pouring cylinder) | Geospec 3 - Test Method 11.1 | 6.68 | 2511 | | A ² | A ² | A ² | A ² | A ² |
| GSP 11.2 | Determination of in-situ bulk density and in-situ dry density of soils by the sand replacement methods (with large pouring cylinder) | Geospec 3 - Test Method 11.2 | 6.68 | 2511 | | A ² | A ² | A ² | A ² | A ² |
| GSP 11.3 | Determination of in-situ bulk density of soils by nuclear densometer | Geospec 3 - Test Method 11.3 | 6.68 | 2511 | | √ | | √ | √ | |
| GSP 11.4 | Determination of relative compaction of fill materials | Geospec 3 - Test Method 11.4 | 6.68, 9.44 | 2511 | | A | A | A | A | A |
| GSP 12.1 | Determination of california bearing ratio (CBR) | Geospec 3 - Test Method 12.1 | | | A | | | | | |
| GSP 14.1 | The one-dimensional consolidation test | Geospec 3 - Test Method 14.1 | | | A | | | | | |
| GSP 14.2 | The isotropic compression test in a triaxial cell | Geospec 3 - Test Method 14.2 | | | A | | | | | |
| GSP 15.1 | The unconsolidated undrained triaxial compression test without pore pressure measurement | Geospec 3 - Test Method 15.1 | | | A | | | | | |
| GSP 15.2(a) | The isotropically consolidated undrained triaxial compression test with pore pressure measurement (single-stage) | Geospec 3 - Test Method 15.2 | | | A | | | | | |
| GSP 15.2(b) | The isotropically consolidated undrained triaxial compression test with pore pressure measurement (multi-stage) | Geospec 3 - Test Method 15.2 | | | A | | | | | |
| GSP 15.3 | The isotropically consolidated drained triaxial compression test with measurement of volume change | Geospec 3 - Test Method 15.3 | | | A | | | | | |
| GSP 15.4(a) | The isotropically consolidated undrained triaxial compression test with pore pressure measurement of loosely compacted fill | Geospec 3 - Test Method 15.2 with modification | | | A | | | | | |
| GSP 15.5 | Constant-q stress path test | In-house test method | | | √ | | | | | |
| GSP 16.1 | The direct shear test (small shear box apparatus) | Geospec 3 - Test Method 16.1 | | | A | | | | | |
| GSP 16.2 | The direct shear test (large shear box apparatus) | Geospec 3 - Test Method 16.2 | | | A | | | | | |
| GSP 16.3 | Determination of friction between fill material and reinforcement elements | Geospec 3 - Test Method 16.2 with modifications based on Geoguide 6 | | | √ | | | | | |

Steel and other metals

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | |
|-------------|---|--|------------------|--------------------------|-------------------------|----|----|----|----|----|
| | | | | | CL | NL | KL | TP | TS | SS |
| STE 0.0 | Reception of steel bar, wire and fabric | In-house procedure | | | √ | | | | | |
| STE 1.9 | Determination of mass per unit length of steel bars | CS2:1995 | | 2403 | A* | | | | | |
| STE 1.10 | Determination of tensile properties of steel bars | CS2:1995 | | 2403 | A* | | | | | |
| STE 1.11 | Cold bend tests of steel bars | CS2:1995 | | 2403 | A* | | | | | |
| STE 1.12 | Rebend tests of steel bars | CS2:1995 | | 2403 | A* | | | | | |
| STE 1.17 | Determination of mass per unit length of steel reinforcing bars | BS 4449:2005+A2:2009 | | 2403 | √ | | | | | |
| STE 1.18 | Determination of tensile properties of steel reinforcing bars | BS 4449:2005+A2:2009 | | 2403 | √ | | | | | |
| STE 1.19 | Rebend test of steel reinforcing bars | BS 4449:2005+A2:2009 | | 2403 | √ | | | | | |
| STE 1.20 | Determination of mass per unit length of stainless steel bars | BS 6744:2001+A2:2009 | | 2423 | √* | | | | | |
| STE 1.21 | Determination of tensile properties of stainless steel bars | BS 6744:2001+A2:2009 | | 2423 | √* | | | | | |
| STE 1.22 | Bend test of stainless steel bars | BS 6744:2001+A2:2009 | | 2423 | √* | | | | | |
| STE 1.23 | Determination of mass per unit length of steel reinforcing bars | CS2:2012 (Rev. 6) Cl. 6.1 & 6.2 | | 2403 | A | | | | | √ |
| STE 1.24 | Determination of tensile properties of steel reinforcing bars | BS EN ISO 6892-1:2009 in conjunction with CS2:2012 (Rev. 6) Cl. 6.1 & 6.4 | | 2403 | A | | | | | √ |
| STE 1.25 | Rebend test of steel reinforcing bars | CS2:2012 (Rev. 6) Cl. 6.1 & 6.5 | | 2403 | A | | | | | √ |
| STE 1.26 | Determination of the surface geometry (relative rib area only) of ribbed steel reinforcing bars | CS2:2012 (Rev. 6) Cl. 6.1 & 6.7 excluding 6.7.3 with Modification (for 40-50mm dia.) | | 2403 | A | | | | | √ |
| STE 2.5 | Determination of mass, pitch and wire dimension of steel fabric | BS4483:1998 | Table 15.2 | 2421 | √ | | | | | |
| STE 2.6 | Determination of tensile properties of steel fabric | BS4483:1998 | Table 15.2 | 2421 | √ | | | | | |
| STE 2.7 | Rebend test of steel fabric | BS4483:1998 | Table 15.2 | 2421 | √ | | | | | |
| STE 2.8 | Weld shear test of steel fabric | BS4483:1998 | Table 15.2 | 2421 | √ | | | | | |
| STE 2.9 | Determination of mass and pitch of steel fabric | In-house method STE 2.9 in conjunction with BS 4483:2005 Cl.7.3 | | 2421 | A | | | | | |
| STE 2.10 | Determination of tensile properties of steel fabric | ISO 6892:1998 & BS EN ISO 15630-2:2002 Cl.5 in conjunction with BS4483:2005 Cl. 7.2.2, 7.2.3 & 9 | | 2421 | A | | | | | |
| STE 2.11 | Rebend test of steel fabric | BS EN ISO 15630-1:2002 Cl.7 in conjunction with BS4483:2005 Cl. 7.2.2, 7.2.5 & 9 with modification that the test is performed at a rate of bending of about 3 revolutions per minute | | 2421 | A | | | | | |
| STE 2.12 | Weld shear test of steel fabric | BS EN ISO 15630-2:2002 Cl.7 in conjunction with BS4483:2005 Cl. 7.2.2, 7.2.4 & 9 | | 2421 | A | | | | | |
| STE 3.1 | Determination of mass per unit length of cold reduced steel wires | BS4482:1985 Sect 5 | 15.03 & 15.31 | 2423 | √* | | | | | |
| STE 3.2 | Determination of tensile properties of cold reduced steel wires | BS4482:1985 Sect 12 | 15.03 & 15.31 | 2423 | √* | | | | | |
| STE 3.3 | Rebend test of cold reduced steel wires | BS4482:1985 Section 12.2 with modification | 15.03 & 15.31 | 2423 | √* | | | | | |
| STE 3.6 | Determination of actual diameter and actual breaking load of stranded steel wire ropes | BS302-1:Part 1:1987 Appendices A and B | | 2423 | A* | | | | | |
| STE 3.7 | Mechanical testing of mild steel wire | BS 1052:1980 | | 2423 | √* | | | | | |
| STE 3.8 | Determination of mass per metre of steel wires | BS4482:2005 Cl. 7.3 | | 2423 | √* | | | | | |
| STE 3.9 | Determination of tensile properties of steel wires | ISO 6892-1:1998 & BS EN ISO 15630-1:2002 Cl.5 in conjunction with BS4482:2005 Cl. 7.2.2, 7.2.3 & 9 | | 2423 | √* | | | | | |
| STE 3.10 | Rebend test of steel wires | BS EN ISO 15630-1:2002 Cl.7 in conjunction with BS4482:2005 Cl. 7.2.2, 7.2.4 & 9 with modification | | 2423 | √* | | | | | |
| STE 4.2 | Determination of tensile properties of structural section | BS4360:1986 Clause 23.1 | 18.04 & 19.07 | 2420 | A | | | | | |
| STE 4.5 | Determination of tensile properties of steel tube | BS 18-4:1971 in conjunction with BS 1387:1985 Cl. 3.2 | | 2420 | A* | | | | | |
| STE 4.7 | Determination of tensile properties of structural steel | BS EN 10025-1:2004 | | 2420 | A | | | | | |
| STE 4.9 | Determination of tensile properties of hot finished structural hollow sections of non-alloy and fine grain steels, cold formed welded structural hollow sections of non-alloy and fine grain steels | BS EN 10210-1:2006 BS EN 10219-1:2006 | | 2420 | A | | | | | |
| STE 4.10 | Determination of tensile properties of hot rolled sheet piling of non alloy steels | BS EN 10248-1:1996 | | 2420 | √* | | | | | |
| STE 4.11 | Determination of tensile properties of metallic materials | BS EN 10002-1:2001 | | 2420 | A* | | | | | |
| STE 4.12 | Determination of tensile properties of stainless steel sheet/plate and strip Determination of tensile properties of stainless steel bars, rods, wire, sections | BS EN 10002-1:2001 in conjunction with BS EN 10088-2:2005 Cl. 7.4.2 BS EN 10002-1:2001 in conjunction with BS EN 10088-3:2005 Cl. 7.4.2 | | 2420 | A* | | | | | |
| STE 4.13 | Determination of tensile properties of metallic materials | BS EN ISO 6892-1:2019 | | 2420 | A | | | | | |
| STE 4.14 | Determination of tensile properties of non-alloy steel tubes (for Specified outside diameter between 10.2 mm and 60.3 mm) | BS EN 10002-1:2001 in conjunction with BS EN 10255:2004 Cl. 9.3 | | 2420 | A* | | | | | |
| STE 4.15 | Determination of tensile properties of stainless steel sheet/plate and strip / Determination of tensile properties of stainless steel bars, rods, wire and sections | BS EN ISO 6892-1:2019 in conjunction with BS EN 10088-2:2014 Cl. 7.4.2 / BS EN ISO 6892-1:2019 in conjunction with BS EN 10088-3:2014 Cl. 7.4.2 | | 2420 | A* | | | | | |
| STE 5.1 | Determination of dimensions and mass per unit length of 7-wire strands | BS5896:1980 Clause 24.2 | 17.06 | 2423 | A | | | | | |
| STE 5.1(a) | Determination of straightness and deviation from nominal mass per metre of 7-wire strand | BS EN ISO 15630-3:2019 Cl. 16 in conjunction with BS 5896:2012 Cl. 7.2.1 & 9 | | 2423 | √ | | | | | |
| STE 5.2(b) | Determination of tensile properties of 7-wire strands (using clip on extensometer) | BS5896:1980 Sect A5 | 17.06 | 2423 | A | | | | | |
| STE 5.2(c) | Determination of tensile properties of 7-wire strand | BS EN ISO 6892-1:2019 Cl. 10.3.3 Method B & BS EN ISO 15630-3:2019 Cl. 5 in conjunction with BS 5896:2012 Cl. 7.2.2 & 9 | | 2423 | √ | | | | | |
| STE 6.1 | Determination of mass of manhole covers and gully gratings | In-house test method | | 2405 | A* | | | | | |
| STE 6.2 | Determination of resistance to fracture of manhole covers and gully gratings | Cl. 5.95(2) & App.5.3 of GS(2006) | 5.95 App. 5.3 | 2405 | A* | | | | | |
| STE 6.3 | Bending test of manhole steps | BS 1247-1:1990 App. A | 5.26 | 2422 | A | | | | | |
| STE 6.3(a) | Vertical loading test of steps for underground man entry chambers | BS EN 13101:2002 Annex B in conjunction with BS EN 13101:2002 Cl. 4.3.7 | | 2422 | √ | | | | | |
| STE 6.4 | Twist test of manhole steps | BS 1247-1:1990 Cl. 7.1 | 5.26 | 2422 | A | | | | | |
| STE 6.4(a) | Twist test of steps for underground man entry chambers | BS EN 13101:2002 Annex A in conjunction with BS EN 13101:2002 Cl. 4.3.6 | | 2422 | √ | | | | | |
| STE 6.5 | Pull-out test of manhole steps | BS 1247-1:1990 App. B | 5.26 | 2422 | A | | | | | |
| STE 6.5(a) | Pull out test of steps for underground man entry chambers | BS EN 13101:2002 Annex D in conjunction with BS EN 13101:2002 Cl. 4.3.9 | | 2422 | √ | | | | | |
| STE 6.11 | Determination of the ultimate breaking load of bolts / screws / thread rod and nuts | In-house test method | | 2418 | √* | | | | | |
| STE 6.12 | Determination of the Tensile Properties of Corrosion-resistant Stainless Steel Fasteners (from M8 to M39 nominal size) | ISO 82:1974 and ISO 898-1:1978 in conjunction with BS 6105:1981 Cl. 6.1 to Cl. 6.4 | | 2418 | √* | | | | | |
| STE 6.13 | Proof load test for ISO metric precision hexagon steel nuts | BS 3692 : 1967 Appendix E.1 to E.3 | | 2418 | A* | | | | | |
| STE 6.13(a) | Proof load test for ISO metric precision hexagon steel nuts | BS 3692: 2001 Annex C.1 to C.3 | | 2418 | A* | | | | | |
| STE 6.14 | Permanent elongation test and tensile test of reinforcement connectors for tension joints | In-house Method STE 6.14 in conjunction with GS (2006) Vol. 2 Cl. 15.35 and COP for Structural Use of Concrete (2004) Cl. 3.2.8.2 | 15.35 | 2413 | A | | | | | |
| STE 6.14(a) | Permanent elongation test and tensile test of reinforcement connectors for tension joints | In-house Method STE 6.14(a) in conjunction with GS (2020) Vol. 2 Cl. 15.35 | 15.35 | 2413 | √ | | | | | |
| STE 6.15(b) | Determination of tensile strength of ISO Metric Precision Hexagon Bolts and Screws (from M8 to M39 nominal size) | BS 18:1987 in conjunction with BS 3692:1967 Appendix D.2 | | 2418 | A* | | | | | |
| STE 6.15(c) | Determination of tensile strength of ISO metric precision hexagon bolts and screws (from M8 to M39 nominal size) | ISO 6892:1998 and BS EN ISO 898-1:1999 Cl. 8.2 in conjunction with BS 3692:2001 Cl. 13 | | 2418 | A* | | | | | |
| STE 6.17 | Static testing on steel parapet post | BS 6779:Part 1:1998 with modification | | 2419 | √* | | | | | |

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | | |
|-------------|---|--|-----------|--------------------------|-------------------------|----|----|----|----|----|--|
| | | | | | CL | NL | KL | TP | TS | SS | |
| STE 6.22 | Loading test for surface boxes, for gas and waterworks purposes | BS 5834-2:1983 App. A with Modifications | | 2405 | A [#] | | | | | | |
| STE 6.23 | Loading test of gully tops and manhole tops for vehicular and pedestrian areas. Determination of mass for gully tops and manhole tops | Cl.8 of BS EN 124: 1994 | | 2405 | A [#] | | | | | | |
| STE 6.24 | Testing of mechanical connector systems for steel reinforcing bars | AC133 : 2008 with modification | | 2413 | A [#] | | | | | | |
| STE 6.25 | Testing of mechanical couplers | In-house Method STE 6.25 in conjunction with COP for Structure Use of Concrete (2013) Cl. 3.2.8.3 and AC 133:2008 in conjunction with COP for Structure Use of Concrete (2013) Cl. 3.2.8.4 | | 2413 | A | | | | | | |
| STE 6.26 | Charpy 'V' notch impact test on metallic materials | BS EN 10045:1990 | | 2420 | | | | | | | |
| STE 6.26(a) | Charpy 'V' notch pendulum impact test on metallic materials | BS EN ISO 148-1:2016 | | 2420 | | | | | | | |
| STE 6.27 | Determination of the tensile properties of corrosion-resistant stainless steel fasteners (from M8 to M39 nominal size) | ISO 6892:1998 and ISO 898-1:1988 Cl. 8.2 in conjunction with BS EN ISO 3506-1:1998 Cl. 6.2.1 to Cl. 6.2.4 | | 2418 | √ [#] | | | | | | |
| STE 6.27(a) | Determination of the tensile properties of corrosion-resistant stainless steel fasteners (from M8 to M39 nominal size) | ISO 6892-1:2019 and ISO 898-1:2013 Cl. 9.2 in conjunction with BS EN ISO 3506-1:2009 Cl. 7.2.1 to Cl. 7.2.4 | | 2418 | A [#] | | | | | | |
| STE 6.27(b) | Determination of the tensile properties of corrosion-resistant stainless steel fasteners (from M8 to M39 nominal size) | BS EN ISO 6892-1:2019 in conjunction with BS EN ISO 3506-1:2020 Cl. 9.1 | | 2418 | A [#] | | | | | | |
| STE 6.28 | Determination of tensile strength of ISO metric black hexagon bolts and screws (from M8 to M39 nominal size) | BS 18:1987 in conjunction with BS 4190:1967 Appendix A.2 | | 2418 | √ [#] | | | | | | |
| STE 6.28(a) | Determination of tensile strength of ISO metric black hexagon bolts and screws (from M8 to M39 nominal size) | ISO 6892:1998 and BS EN ISO 898-1:1999 Cl. 8.2 in conjunction with BS 4190:2001 Cl. 15 | | 2418 | A [#] | | | | | | |
| STE 6.28(b) | Determination of tensile strength for ISO metric black hexagon bolts and screws (from M8 to M39 nominal size) | BS EN ISO 6892-1:2019 and BS EN ISO 898-1:2013 Cl. 9.2 in conjunction with BS 4190:2014 Cl. 21 | | 2418 | A [#] | | | | | | |
| STE 6.29 | Determination of tensile strength for fasteners made of carbon steel and alloy steel (from M8 to M39 nominal size) | ISO 6892:1998 in conjunction with BS EN ISO 898-1:1999 Cl. 8.2 | | 2418 | √ [#] | | | | | | |
| STE 6.30 | Proof load test for ISO metric black hexagon steel nuts | BS 4190: 1967 Appendix B.1 | | 2418 | √ [#] | | | | | | |
| STE 6.30(a) | Proof load test for ISO metric black hexagon steel nuts | BS 4190: 2001 Annex A.1 | | 2418 | A [#] | | | | | | |
| STE 6.30(b) | Proof load test for ISO metric black hexagon steel nuts (from M8 to M39 nominal size) | BS 4190:2014 Annex A.1 to A.3 | | 2418 | A [#] | | | | | | |
| STE 6.31 | Proof load test for high tensile steel nuts for structural engineering metric series - general grade (from M12 to M36 nominal size) | BS 4395-1:1969 Cl. 3.3 & Appendix C.1 to C.3 | | 2418 | √ [#] | | | | | | |
| STE 6.32 | Proof load test for corrosion-resistant stainless steel nuts (from M8 to M39 nominal size) | ISO 898/II in conjunction with BS 6105:1981 Cl. 6.6 | | 2418 | √ [#] | | | | | | |
| STE 6.33 | Proof load test for corrosion-resistant stainless steel nuts (from M8 to M39 nominal size) | BS EN ISO 898-2:1992 Cl. 8.1 and BS EN ISO 898-6:1996 Cl. 8.1 in conjunction with BS EN ISO 3506-2:1998 Cl. 6.2 | | 2418 | √ [#] | | | | | | |
| STE 6.33(a) | Proof load test for corrosion-resistant stainless steel nuts (from M8 to M39 nominal size) | BS EN ISO 898-2:2012 Cl. 9.1 and BS EN ISO 898-6:1996 Cl. 8.1 in conjunction with BS EN ISO 3506-2:2009 Cl. 7.2 | | 2418 | A [#] | | | | | | |

Timber

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | | |
|-----------|-----------------------------------|------------------------------|-----------|--------------------------|-------------------------|----|----|----|----|----|--|
| | | | | | CL | NL | KL | TP | TS | SS | |
| TIM 1.1 | Determination of moisture content | BS373:1957 Section 2 | 21.92 | 2425 | √ [#] | | | | | | |
| TIM 1.2 | Determination of density | BS373:1957 Section 5 | 21.92 | 2425 | √ [#] | | | | | | |
| TIM 2.2 | Static bending test | BS373:1957 Section 6 | 21.92 | 2425 | √ [#] | | | | | | |
| TIM 2.3 | Janka indentation test | BS373:1957 Section 9 | 21.92 | 2425 | √ [#] | | | | | | |
| TIM 2.4 | End face compression test | BS373:1957 Section 8a and 8b | 21.92 | 2425 | √ [#] | | | | | | |
| TIM 2.5 | Shear test (parallel to grain) | BS373:1957 Section 10 | 21.92 | 2425 | √ [#] | | | | | | |

Thermoplastic road marking materials

| PWLTM No. | Test Description | Method | GS Clause | Test Request Form Number | Availability of Testing | | | | | | |
|-----------|--|--|-----------|--------------------------|-------------------------|----|----|----|----|----|--|
| | | | | | CL | NL | KL | TP | TS | SS | |
| TPL 0.0 | Sampling and preparation | BS3262:Part 1:1989App. B | 12.23 | | √ | | | | | | |
| TPL 1.7 | Determination of thickness of thermoplastic road marking | BS 3262:Part 3:1989 App. B (Micrometer method) | 12.23 | 2426 | √ [#] | | | | | | |
| TPL 1.8 | Determination of the softening point of thermoplastic road marking materials | Annex F in BS EN 1871: 2000 | | 2426 | √ [#] | | | | | | |